

R134a LBP M/HBP 12/24V

产品系列 Serial	产品型号 Model	Displacement 工作容积 (cm ³)	转速 Rotate Speed	制冷量 Capacity			性能系数		Oil charge 注油量 ml	冷却方式 Cooling	Power Supply 电源	Certificate 认证
				测试工况 Test Conditions: -23.3°C(-10F)			COP	EER				
				W	Kcal/h	Btu/h	W/W	Btu/Wh				
L	QDZH15G	1.5	2000	30	26	102	0.95	3.24	130	F	12/24V (DC)	CE
			2500	35	30	120	0.96	3.27				
			3000	42	36	143	0.96	3.27				
			3500	50	44	170	1.00	3.41				
	QDZH20G	2.0	2000	40	34	136	0.98	3.34				
			2500	48	41	163	0.98	3.34				
			3000	57	49	194	1.00	3.41				
			3500	65	56	221	1.00	3.41				
	QDZH25G	2.5	2000	43	37.2	146	1.08	3.68				
			2500	53	46	186	1.05	3.58				
			3000	62	54	211	1.06	3.62				
			3500	72	62	245	1.04	3.55				
	QDZH30G	3.0	2000	52	45	176	1.05	3.58				
			2500	64	55	217	1.05	3.58				
			3000	75	64	254	1.06	3.62				
			3500	87	75	295	1.04	3.55				
	QDZH35G	3.5	2000	60	52	205	1.08	3.68				
			2500	73	63	249	1.07	3.65				
			3000	86	74	293	1.06	3.62				
			3500	100	87	341	1.05	3.58				
	QDZH43G	4.3	2000	80	69	273	1.15	3.92				
			2500	96	83	328	1.20	4.09				
			3000	115	99	392	1.25	4.27				
			3500	138	119	471	1.25	4.27				
MK	QDZH50G	5.0	2000	87	75	297	1.17	3.99	180			
			2500	104	90	355	1.13	3.86				
			3000	130	112	444	1.35	4.61				
			3500	163	141	556	1.20	4.09				
	QDZH65G	6.5	2000	120	104	409	1.20	4.09				
			2500	150	130	512	1.20	4.09				
			3000	180	156	614	1.20	4.09				
			3500	210	181	717	1.20	4.09				
	QDZH75G	7.5	2000	146	125	499	1.20	4.09				
			2500	183	156	625	1.20	4.09				
			3000	220	189	752	1.20	4.09				
			3500	256	219	875	1.20	4.09				
	QDZH91G	9.1	2000	180	154	615	1.20	4.09				
			2500	225	193	769	1.20	4.09				
			3000	270	231	923	1.20	4.09				
			3500	315	270	1077	1.20	4.09				